

08-14-2000

A

EXPRESS MAIL CERTIFICATE

Date 8/11/00 Label No. 628222026

I hereby certify that, on the date indicated above I deposited this paper or fee with the U.S. Postal Service & that it was addressed for delivery to the Assistant Commissioner for Patents, Washington, DC 20231 by "Express Mail Post Office to Addressee" service.

Name (Print) D B Perk Signature [Signature]

PLEASE CHARGE ANY DEFICIENCY UP TO \$300.00 OR
CREDIT ANY EXCESS IN THE FEES DUE WITH THIS
DOCUMENT TO OUR DEPOSIT ACCOUNT NO. 04-0100

DARBY & DARBY P.C.

805 Third Avenue
New York, New York 10022
212-527-7700

Docket No: 6727/OH530

Box PATENT APPLICATION
Assistant Commissioner for Patents
Washington, DC 20231

Sir:

Enclosed please find an application for United States patent as identified below:

Inventor/s (name ALL inventors): Yaron LEDERMAN and Galit VOLPERT

Title: **AUTOMATIC IMPLEMENTATION OF NETWORK CONFIGURATION CHANGES**

including the items indicated:

1. Specification and 26 claims: 3 indep.; 23 dep.; _ multiple dep.
2. ☐ Executed declaration and power of attorney
☒ Unexecuted declaration and power of attorney
3. ☒ Formal drawings, 3 sheets (Figs. 1 - 3)
☐ Informal drawings, _ sheets (Figs.)
4. ☐ Assignment for recording to:

08/11/00
JC904 U.S. PTO

JC941 U.S. PTO
09/637300
08/11/00

09637300-001100

5. ☐ Verified Statement Claiming Small Entity Status
6. ☐ Check in amount of \$.00, (\$ filing; \$ recording)
(See attached **Fee Computation Sheet**)
7. ☐ Preliminary Amendment
8. ☐ Information Disclosure Statement
9. ☐ Please amend the description by inserting the following paragraph after the line containing the title on page 1:
"This patent application claims the priority of U.S. provisional patent application No. 60/, which is incorporated herein by reference."


Priority is claimed for this application, corresponding application/s having been filed as follows:

Country: NONE
Number:
Date:

The priority documents ☐ are enclosed
☐ will follow.

Date: August 11, 2000

Respectfully submitted,



S. Peter Ludwig, Esq.
Reg. No. 25,531
Attorney for Applicant(s)

PATENT FEE COMPUTATION SHEET

	No. of Claims Presented	Extra Claims Previously Paid For	Number of Extra Claims	Rate
Basic Fee				\$690.00
Total Claims	26 - 20	- 0 = 6	x \$18.00	\$108.00
Independent Claims	3 - 3	- 0 = 0	x \$78.00	\$0.00
Multiple Dependent Claims		- if so, add	\$260.00	\$0.00
Surcharge for late submission of filing fee and/or declaration (\$130.00)				\$0.00
SUBTOTAL				\$0.00
[] Small Entity REDUCTION (Half of Subtotal)				\$0.00
Fee for recordation of assignment (\$40.00)				\$0.00
Charge for filing non-English language application (\$130.00)				\$0.00
TOTAL				\$798.00

38540S2

EXPRESS MAIL CERTIFICATE

8/11/00 628222026

I hereby certify that, on the date indicated above I deposited this paper or fee with the U.S. Postal Service & that it was addressed for delivery to the Commissioner of Patents & Trademarks, Washington, D.C. 20231 by "Express Mail Post Office to Addressee's Bank"

Name (Print)

Signature

AUTOMATIC IMPLEMENTATION OF NETWORK CONFIGURATION CHANGES

FIELD OF THE INVENTION

The present invention relates generally to communication networks, and specifically to automated management of network connections.

BACKGROUND OF THE INVENTION

In modern networks, such as Asynchronous Transfer Mode (ATM) networks, the elements of the network use a management information base (MIB) to maintain common status and configuration information. The ATM MIB, for example, holds information concerning virtual path connections (VPCs), virtual channel connections (VCCs), registered services, registered ATM network prefixes and addresses, and capabilities available at ATM interfaces. All of the ATM devices in the network, such as switches and end-systems, use the MIB to determine how to conduct their network communications.

In order to set up and maintain the MIB, the different ATM devices must exchange management information regarding status and configuration conditions. A variety of different methods and protocols for this information exchange have been developed. One commonly-used method is provided in the Integrated Local Management Interface (ILMI) Specification, Version 4.0, published by the ATM Forum Technical Committee (publication no. af-ilmi-0065.00, September, 1996), which is incorporated herein by reference. ILMI supports bi-directional exchange of ATM interface parameters between a pair of connected ATM interface management entities (IMEs), so that each of the pair of IMEs can access the ATM interface MIB of its counterpart. Each

00637300-034100

pair typically includes a network-side IME and a user-side IME (although within the network there are also symmetric IME pairs). When a network device, such as a switch, has multiple ATM interfaces, it will likewise have multiple IMEs, one for each interface.

When a change occurs in configuration or status information held by one of the IMEs in a pair, it sends a trap packet to its counterpart in order to report the change. Trap packets are the means specified by the Simple Network Management Protocol (SNMP) for reporting extraordinary events in a network. SNMP is defined in Request for Comments (RFC) 1157 of the Internet Engineering Task Force (IETF), and is used by ILMI in management and control operations across ATM interfaces. Ordinarily, when the counterpart IME receives the trap packet, it reads the pertinent information from the sending IME in order to determine the configuration and status changes that have occurred. Trap packets are sent using the User Datagram Protocol (UDP), which generally provides fast service but does not guarantee reliable delivery. Therefore, each IME periodically polls its counterpart in order to ensure that no traps have been missed.

Digital Subscriber Line (DSL) is a modem technology that enables broadband digital data to be transmitted over twisted-pair wire, which is the type of infrastructure that links most home and small business subscribers to their telephone service providers. DSL modems enable users to access digital networks at speeds tens to hundreds of times faster than current analog modems and basic ISDN service. DSL thus opens the most critical bottleneck in local-loop access to high-speed

networks, and thus enables ATM service to be extended to client premises equipment (CPE) without requiring major investments in new infrastructure. A range of DSL standards have been defined, known generically as "xDSL," wherein the various standards have different data rates and other associated features but share common principles of operation.

DSL subscribers are connected to high-speed core networks through Digital Subscriber Line Access Multiplexer (DSLAM) systems. Because of the high cost of network bandwidth, a single DSLAM is typically designed to serve between 100 and 1000 clients and to concentrate their traffic through one or a few network trunks. (In the context of the present patent application, the inverse of the number of clients served by a multiplexer - between 1:100 and 1:1000 in the case of the typical DSLAM - is referred to as its concentration ratio.) Thus, to accord with the ILMI model described above, the DSLAM must maintain as many as 1000 network-side IMEs in order to serve all of its clients. As network use grows in the future, this figure may grow even higher. Concentration ratios of this magnitude were not envisioned when the ILMI standard was developed. Adherence to the conventional ILMI model under these conditions would require both the DSLAM and the CPE to dedicate an excessive amount of computing power to interface management.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide improved methods and systems for network information management, particularly in the context of ATM interface management.

It is a further object of some aspects of the present invention to provide methods of network interface management that are suited for use in access multiplexing systems that serve large numbers of clients.

In preferred embodiments of the present invention, an access multiplexer, such as a DSLAM, provides access to a high-speed network, such as an ATM network, to a large number of subscribers, each maintaining respective client premises equipment (CPE). The multiplexer notifies the CPE of a change in network configuration or status by sending an appropriate trap packet to the CPE. In response to the trap packet, the CPE reads all of the relevant information in the MIB held by the multiplexer. The CPE then replaces the information in its own MIB accordingly. The multiplexer regards the read request that it receives from the CPE as an acknowledgment of the trap. When the multiplexer fails to receive the read request within a specified time limit, it resends the trap packet or, if necessary, resets its link with the CPE.

Thus, the multiplexer verifies that every trap it sends is actually delivered to the CPE, despite the unreliable protocol used to send the trap packet. Consequently, it is not necessary for the CPE to poll the multiplexer, as in ILMI and other conventional network management models. This approach substantially reduces the computing burden placed on the multiplexer, as well

38540S2

as simplifying the functionality of the CPE, by obviating the need for the CPE to poll the DSLAM and for the DSLAM to handle polling requests by hundreds or thousands of CPEs.

There is therefore provided, in accordance with a preferred embodiment of the present invention, a method for network management, including:

sending a trap message from a network end switch to client premises equipment (CPE) over a network connection therebetween, informing the CPE of a change in a network management information base (MIB) of the end switch;

receiving a request from the CPE to the end switch, subsequent to the trap message, to read information from the MIB;

providing the information from the end switch to the CPE responsive to the request; and

determining the change to have been implemented by the CPE based on the request to read the information.

Preferably, the CPE replaces old information recorded in a user MIB of the CPE with the information provided from the end switch, wherein the CPE replaces the old information with the provided information substantially in its entirety, without parsing the information for changes.

Further preferably, receiving the request includes awaiting the request for a predetermined period of time, and sending the trap message includes re-sending the trap message if the request is not received within the predetermined period. Most preferably, re-sending the trap message includes making a predetermined number of attempts to re-send the trap message, and including sending a cold start message from the end switch to the

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram that schematically illustrates a network access multiplexing system, in accordance with a preferred embodiment of the present invention;

Fig. 2 is a block diagram that schematically illustrates interface management entities in the system of Fig. 1, in accordance with a preferred embodiment of the present invention; and

Fig. 3 is a flow chart that schematically illustrates a method for updating network configuration information held by client premises equipment, in accordance with a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Fig. 1 is a block diagram that schematically illustrates a network access multiplexing system 20, in accordance with a preferred embodiment of the present invention. A DSLAM 22 comprises multiple interface connections, providing access to a network 24 for a plurality of subscribers having respective client premises equipment (CPE) 26. Network 24 preferably comprises an ATM network, and CPE 26 is configured to provide ATM service directly to the subscriber premises.

Fig. 2 is a block diagram that schematically shows interface management features of DSLAM 22 and of one of CPEs 26, in accordance with a preferred embodiment of the present invention. In accordance with the ILMI model, the connection between DSLAM 22 and CPE 26 is managed by a pair of IMEs: a network-side IME 30 maintained by the DSLAM, and a user-side IME 32 maintained by the CPE. The IMEs typically comprise central processing units (CPUs) running suitable network management software (frequently in addition to other tasks carried out by the CPUs). IMEs 30 and 32 maintain respective MIBs 36 and 38 in memory associated with the CPUs. The MIBs hold network configuration and status information, including tables of VPCs, VCCs, registered services, etc., as is known in the art. A similar pair of IMEs exists for each of the other CPE-DSLAM connections, so that typically, IME 30 is one of between 100 and 1000 IMEs maintained by the DSLAM. In addition, the DSLAM has a network or element management system 34, which serves as its user-side IME vis-a-vis a network device, such as a core switch, with which the DSLAM communicates over a trunk of ATM network 24.

Fig. 3 is a flow chart that schematically illustrates a method by which network IME 30 of DSLAM 22 notifies user IME 32 of CPE 26 of a status or configuration change in MIB 36, in accordance with a preferred embodiment of the present invention. Although this method relates explicitly to VCC changes, it is equally applicable, *mutatis mutandis*, to VPC changes. IME 30 sends a VCC change trap to IME 32, as defined by the ILMI standard, at a trap issuance step 40. Normally, IME 32 receives the trap, and responds with a request to IME 30 to read the service and VCC tables held in MIB 36. User IME 32 does not poll network IME 30. Rather, it simply reads all information from MIB 36 that is associated with the virtual channel (VC) indicated by the VCC change trap. Upon reading this information, IME 32 clears all of the all of the information regarding this virtual channel (VC) from its own MIB 38, and replaces it with the fresh information read from MIB 36. This approach may be less efficient than methods of configuration updating that are used conventionally, but it avoids difficulties that can be caused by having to parse complex changes and thus simplifies the handling of such changes in multi-client environments such as system 20.

When network IME 30 receives the read request from user IME 32, it treats the request as an acknowledgment that IME 32 received the trap packet, at an acknowledgment step 42. Thus, at this point, after IME 32 has read the pertinent information, handling of the status or configuration change by IME 30 is finished.

If at step 42, network IME 30 does not receive a read request from user IME 32 within a specified period

38540S2

and DSLAM systems for communication over such networks, the principles of the present invention are similarly applicable to management of other types of networks, such as Internet Protocol (IP) networks. It will thus be appreciated that the preferred embodiment described above is cited by way of example, and that the present invention is not limited to what has been particularly shown and described hereinabove. Rather, the scope of the present invention includes both combinations and subcombinations of the various features described hereinabove, as well as variations and modifications thereof which would occur to persons skilled in the art upon reading the foregoing description and which are not disclosed in the prior art.

CLAIMS

1. A method for network management, comprising:
 - sending a trap message from a network end switch to client premises equipment (CPE) over a network connection therebetween, informing the CPE of a change in a network management information base (MIB) of the end switch;
 - receiving a request from the CPE to the end switch, subsequent to the trap message, to read information from the MIB;
 - providing the information from the end switch to the CPE responsive to the request; and
 - determining the change to have been implemented by the CPE based on the request to read the information.
2. A method according to claim 1, wherein the CPE replaces old information recorded in a user MIB of the CPE with the information provided from the end switch.
3. A method according to claim 2, wherein the CPE replaces the old information with the provided information substantially in its entirety, without parsing the information for changes.
4. A method according to claim 1, wherein receiving the request comprises awaiting the request for a predetermined period of time, and wherein sending the trap message comprises re-sending the trap message if the request is not received within the predetermined period.
5. A method according to claim 4, wherein re-sending the trap message comprises making a predetermined number of attempts to re-send the trap message, and comprising sending a cold start message from the end switch to the CPE to reset the connection if the request is not

received after the predetermined number of attempts have been made.

6. A method according to claim 1, wherein the network connection comprises an Asynchronous Transfer Mode (ATM) network connection.

7. A method according to claim 6, wherein sending the trap message comprises sending an ATM Integrated Local Management Interface (ILMI) trap message.

8. A method according to claim 7, wherein the trap message comprises a virtual channel connection (VCC) trap.

9. A method according to claim 7, wherein the trap message comprises a virtual path connection (VPC) trap.

10. A method according to claim 6, wherein the network end switch comprises an access multiplexer, and wherein the CPE comprises one of a plurality of client equipment installations serviced by the multiplexer.

11. A method according to claim 10, wherein the access multiplexer comprises a Digital Subscriber Line Access Multiplexer (DSLAM).

12. A method according to claim 11, wherein the DSLAM is adapted to service at least one hundred of the client equipment installations.

13. A method according to claim 1, wherein sending the trap message comprises sending multiple trap messages regarding multiple changes in the MIB, and wherein receiving the request comprises receiving multiple read requests from the CPE to read the information from the MIB, each such read request subsequent to a respective one of the trap messages, and

38540S2

change in a network management information base (MIB) of the end switch, and responsive to the trap message, to read information from the MIB without polling the end switch for further trap messages.

25. Equipment according to claim 24, wherein the CPE maintains a user MIB, and is adapted to replace old information recorded in the user MIB with the information read from the end switch.

26. Equipment according to claim 25, wherein the CPE is adapted to replace the old information with the read information substantially in its entirety, without parsing the information for changes.

ABSTRACT

A method for network management includes sending a trap message from a network end switch to client premises equipment (CPE) over a network connection therebetween, informing the CPE of a change in a network management information base (MIB) of the end switch. A request from the CPE to the end switch, subsequent to the trap message, to read information from the MIB, and the information is provided from the end switch to the CPE responsive to the request. The change is determined to have been implemented by the CPE based on the request to read the information. There is thus no need for the CPE to poll the processor for further trap messages.




FIG. 1

FIG. 2





FIG. 3



**DECLARATION
AND POWER OF ATTORNEY
Original Application**

As a below named inventor, I declare that the information given herein is true, that I believe that I am the original, first and sole inventor if only one name is listed at 1 below, or a joint inventor if plural inventors are named below, of the invention entitled:

AUTOMATIC IMPLEMENTATION OF NETWORK CONFIGURATION CHANGES

which is described and claimed in:

[X] the attached specification or ☐ the specification in application
Serial No. , filed
(for declaration not accompanying appl.)

that I do not know and do not believe that the same was ever known or used in the United States of America before my or our invention thereof or patented or described in any printed publication in any country before my or our invention thereof, or more than one year prior to this application, or in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months prior to this application, that I acknowledge my duty to disclose information of which I am aware which is material to patentability in accordance with 37 CFR §1.56. I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I hereby claim the priority benefits under 35 U.S.C. §119 of any application(s) for patent or inventor's certificate listed below. All foreign applications for patent or inventor's certificate on this invention filed by me or my legal representatives or assigns prior to the application(s) of which priority is claimed are also identified below.

PRIOR APPLICATION(S), IF ANY, OF WHICH PRIORITY IS CLAIMED

<u>COUNTRY</u>	<u>APPLICATION NO.</u>	<u>DATE OF FILING</u>
----------------	------------------------	-----------------------

**ALL FOREIGN APPLICATIONS, IF ANY, FILED PRIOR
TO THE APPLICATION(S) OF WHICH PRIORITY IS CLAIMED**

COUNTRY APPLICATION NO. DATE OF FILING

POWER OF ATTORNEY:

As a named inventor, I hereby appoint the following attorney(s) and/or agents(s) to prosecute this application and transact all business in the Patent and Trademark office connected therewith: Gordon D. Coplein #19,165, William F. Dudine, Jr. #20,569, Michael J. Sweedler #19,937, S. Peter Ludwig #25,351, Paul Fields #20,298, Marc S. Gross #19,614, Joseph B. Lerch #26,936, Melvin C. Garner #26,272, Ethan Horwitz #27,646, Beverly B. Goodwin #28,417, Adda C. Gogoris #29,714, Martin E. Goldstein #20,869, Bert J. Lewen #19,407, Henry Sternberg #22,408, Peter C. Schechter #31,662, Robert Schaffer #31,194, Robert C. Sullivan, Jr. #30,499, Ira J. Levy #35,587, Joseph R. Robinson #33,448, Scott G. Lindvall #40,325

all of the firm of DARBY & DARBY P.C., 805 Third Avenue, New York, NY 10022

SEND CORRESPONDENCE TO:

DARBY & DARBY P.C.
805 Third Avenue
New York, NY 10022

DIRECT TELEPHONE CALLS TO:

S. Peter Ludwig, Esq.

212-527-7700

FULL NAME AND RESIDENCE OF INVENTOR 1

LAST NAME: **LEDERMAN** FIRST NAME: **YARON** MIDDLE NAME:

CITY: **Ramat-Gan** STATE OR FOREIGN COUNTRY: **Israel** COUNTRY OF CITIZENSHIP: **Israel**

POST OFFICE ADDRESS: **21 Etzel Street** CITY: **Ramat-Gan** STATE OR COUNTRY: **Israel** ZIP CODE: **52263**

FULL NAME AND RESIDENCE OF INVENTOR 2

LAST NAME: **VOLPERT** FIRST NAME: **GALIT** MIDDLE NAME:

CITY: **Petach-Tikva** STATE OR FOREIGN COUNTRY: **Israel** COUNTRY OF CITIZENSHIP: **Israel**

POST OFFICE ADDRESS: **12 Ein Gedi Street** CITY: **Petach-Tikva** STATE OR COUNTRY: **Israel** ZIP CODE: **49256**

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001

SIGNATURE OF INVENTOR 2: _____ DATED: _____
Galit VOLPERT